

# Daraclean® 282

DISTRIBUÉ PAR / DISTRIBUTED BY:

**QUEBEC**164, St-Jean-Baptiste  
Mendier, QC J6R 2C2  
450-691-9090  
info@qn-de.ca**ONTARIO**275, Sheldon Drive, Unit 3  
Cambridge, ON N1T 1A3  
519-894-9090  
nadams@qn-de.ca**ALBERTA**7307, 50 street NW  
Edmonton, AB T6B 2J9  
987-689-6811  
lfields@qn-de.ca

www.qn-de.ca

1-800-361-3630

## Alkaline Aqueous Cleaner

A low-foaming, all-purpose alkaline cleaning solution, Daraclean® 282 is an excellent cleaner for a broad spectrum of soils.

This multi-purpose industrial cleaner has excellent soil-rejecting properties and suspends soils until they settle and can be removed by filtering or skimming, for a cleaning bath which lasts much longer than other water-based cleaners.

Daraclean 282 can be used in concentrations up to 25 percent (20 percent for CARB compliance) in immersion, ultrasonic, spray and steam applications.

Moderately alkaline, with low foam levels, Daraclean 282 contains inhibitors to prevent metal corrosion, and has no phosphates and is hard water tolerant.

Daraclean 282 meets all major aerospace specifications for NDT cleaning, is safe to use on most metals and is non-aggressive on aluminum, magnesium and titanium alloys.



## BENEFITS

### Maximize range of use

- Effectively cleans a wide variety of soils and contaminants from parts
- Approved for NDT pre-cleaning due to low silicates and low residue
- Conforms to all major aerospace requirements
- Works with most application methods and equipment for increased flexibility
- Added corrosion inhibitors protect parts and equipment against rust

### Maximize operator comfort and safety

- Promotes better inspection quality by providing the operator with a more comfortable work environment
- Reduces discomfort from strong odors
- Exceeds all EHS requirements

## FEATURES

- Multi-purpose alkaline cleaner
- Low foam level
- Aerospace compliant
- Works on a wide range of materials
- Cleans a broad spectrum of soils
- Multi-metal safe
- Low silicates
- Low residue

## APPLICATIONS

### Cleaning methods:

- Dipping / immersion cleaning
- Ultrasonic cleaning
- Spray cleaning
- Steam cleaning

### Ideal for:

- Aluminum
- Anodized aluminum
- Brass and bronze
- Carbon steel
- Cast iron
- Stainless steel
- Copper
- Magnesium
- Nickel
- Superalloys
- Plated metals
- Titanium

### Removes:

- Buffing compounds
- Carbonized soils
- Cutting fluids
- Heavy oils and dirt
- Lubricant oils
- Machine oils
- Machining fluid
- Medium weight and lube oil
- Motor oil
- Synthetic coolant
- Water-soluble oils

### Applications:

Excellent	••••	Aluminum	Anodized Aluminum	Brass & Bronze	Carbon Steel & Cast Iron	Copper	Magnesium	Nickel & Superalloys	Plating (Cd, Cr, Ir, Pt)	Stainless Steel	Titanium	Zinc
Good	•••											
Fair	••											
Poor	•											
Not Recommended												
Water-Soluble Oils	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Machining Fluid	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Synthetic Coolants	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Medium Weight Oils	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Lube Oils	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Buffing Compounds	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Motor Oils	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Heavy Petroleum Oils	••••	••••	••••	••••	••••	••••	•••	••••	••••	••••	•••	
Carbonized Soils	•••	•••	•••	•••	•••	•••	••	•••	•••	•••	••	
Railroad & Axle Grease												
Glues												
Spray Adhesives												

## SPECIFICATION COMPLIANCE

- AMS 1551, 1551A
- ARP 1512
- ASTM F945, F519 TYPE 1 C
- BAC 5763
- Boeing D6-48809
- CSS 253
- GEAE Method 22, 51145
- Honeywell ARP 4992
- Pratt and Whitney PMC 1429
- PWA 36604
- PWA K231
- RR CSS 204 Type A

## PROPERTIES

<b>pH Level</b>	Alkaline
<b>Foam Level</b>	Low
<b>Silicates</b>	Yes
<b>Phosphates</b>	No
<b>Hard Water Tolerance</b>	Moderate
<b>Aerospace Compliant</b>	Yes
<b>SCAQMD Certified</b>	No

## USE RECOMMENDATIONS

Cleaning Method	Concentration	Temp.	Typical Duration
Immersion	3–25%	80 to 180°F / 27 to 82°C	2–30 mins
Ultrasonic	3–25%	80 to 180°F / 27 to 82°C	2–30 mins
Spray	1–12% Recomm.: 2–5%	130 to 180°F / 54 to 82°C	0.25–3 mins
Steam	1–12%	150 to 200°F / 66 to 93°C	1–5 mins

Storage temperature: 50 to 86°F / 10 to 30°C

## PACKAGING

5 gal / 18.9 L pail 01-6000-40  
NSN 6850-01-364-8328

55 gal / 208 L drum 01-6000-45  
NSN 6850-01-364-8329

## INSTRUCTIONS FOR USE

Dilute cleaner with water to the appropriate concentration or use. Cleaning efficiency can be improved with agitation and heat. Increasing cleaning bath temperature will decrease foaming.

### Maintenance Recommendations

Maintain cleaning bath by skimming and/or filtering. Check in-use cleaner concentration to maintain cleaning effectiveness. The recommended method for measuring concentration is titration method.

Concentration Verification: HACH Alkalinity Titration Kit\*

<b>Titrant</b>	0.5N Sulfuric Acid
<b>Indicator</b>	Bromcresol Green-Methyl Red
<b>Concentration %</b>	Titrant drops x 1.7

\* Ordering info: Alkalinity Test Kit, Model AL-TA; Product # 2314500; Mfr. Hach Company; Website [www.hach.com](http://www.hach.com)

## HEALTH AND SAFETY

Review all relevant health and safety information before using this product. For complete health and safety information, refer to the product Safety Data Sheet, which is available at [www.qnde.ca](http://www.qnde.ca).

DISTRIBUÉ PAR / DISTRIBUTED BY:



QUEBEC  
164, St-Jean-Baptiste  
Mercier, QC J6R 2C2  
T: (450) 691-9090

ONTARIO  
275 Sheldon Drive, Unit 3  
Cambridge, ON N1T 1A3  
T: (519) 894-9069

[www.qnde.ca](http://www.qnde.ca)

# Daraclean Compatibility with Plastics and Elastomers

Aqueous cleaners are known to have adverse effects on some gasket materials while having no effect on others. Adverse effects may include swelling and plasticising (softening) or swelling and disintegration (brittleness). The following lists Daraclean compatibility with a variety of elastomers when tested at 45°C for 92 days.

DARACLEAN		200	212	235	236	259	282	282GF	283
Flourinated Elastomer	Viton	E	E	E	E	E	E	E	E
Fluorinated Elastomer	PVDF	E	E	E	E	E	E	E	E
Flourinated Elastomer	Teflon®	E	E	E	E	E	E	E	E
Fluorinated Elastomer	Kalrez®	E	E	E	E	E	E	E	E
Composite	Ceramics	E	E	E	E	E	E	E	E
Composite	Nickel Graphite	E	E	E	E	E	E	E	E
Fiber	Nylon	E	E	E	E	E	E	E	E
Chloroprene	Neoprene	G	G	G	G	G	G	G	G
Polyvinyl Chloride	PVC	E	E	E	E	E	E	E	E
Isobutylene Isoprene	Butyl	G	G	G	G	G	G	G	G
Ethylene Propylene	E P Rubber	G	G	G	G	G	G	G	G
Polysulfide	Thiokol	G	G	G	G	G	G	G	G
Chlorosulfonated PE	Hypolon	G	G	G	G	G	G	G	G
Chloro Polyvinyl Chloride	CPVC	G	G	G	G	G	G	G	G
Polypropylene	Polypropylene	G	G	G	G	G	G	G	G
E P Diene Monomer	EPDM	G	G	G	G	G	G	G	G
Polyisoprene	Latex (Natural) Rubber	F	F	F	F	F	F	F	F
Syn. Polyisoprene	Latex(Synthetic)Rubber	F	F	F	F	F	F	F	F
Polyester/Polyether	(Poly)Urethane	F	F	F	F	F	F	F	F
Poly Methyl Methacrylate	Plexiglass	F	F	F	F	F	F	F	F
Styrene Butadiene	Buna-S	F	F	F	F	F	F	F	F
Styrene Nitrile Copolymer	Buna-N	F	F	F	F	F	F	F	F

Code:

E = Excellent. No effect.

G = Good. Little or no effect

F = Fair. Slight swelling, softening or brittleness. Switch to an alternate elastomer if possible.

P = Poor. Swelling, softness or brittleness noted. Not recommended for use with Daraclean.

Revised: January 2018

DISTRIBUÉ PAR / DISTRIBUTED BY:

**QNDE**  
QUALITY NDE LTD

QUEBEC

164, St-Jean-Baptiste  
Mercier, QC J6R 2C2  
450-691-9090  
info@qn.de.ca

ONTARIO

275, Sheldon Drive, Unit 3  
Cambridge, ON N1T 1A3  
519-894-9069  
nadams@qn.de.ca

ALBERTA

7307, 50 street NW  
Edmonton, AB T6B 2J9  
587-689-6811  
lfields@qn.de.ca



www.qn.de.ca

1-800-361-3630