ONTARIO 275. Sheldon Drive. Unit 3 7307, 50 street NW Mercier, QC J6R 2C2 Cambridge, ON N1T 1A3 Edmonton, AB T6B 2J9 450-691-9090 519-894-9069 587-689-6811

ALBERTA lfields@qnde.ca

Product Data Sheet

www.qnde.ca

1-800-361-3630

B300

AC Contour Probe

The B300 Contour Probe is a rugged high performance instrument designed for Magnetic Particle inspection to accepted Nondestructive testing standards.

Parker Contour Probes are designed with flexible legs that allow the field to be "focused" at a precise area of inspection. Components are protected by a reinforced glass-filled nylon housing. Model B300 and B300S produce a strong constant AC field.

Plastic carry cases (PL-Case & C-Case) and Test Kits (PL-A Kit & A Kit) are available. Standard test kits include 1 lb. each of Red & Gray powder, PB1 powder blower, and carrying case.

Features

- High-impact, Glass-filled nylon housing
- AC Only
- One year repair/Replacement Guarantee
- Exceeds ASTM lifting standards
- Available with CE certification

Standards Compliance

- ASME Section V, Article 7
- ASTM E709
- **ASTM E1444**
- EN ISO 9934-3 (230V Only)



Applications

Defect location: Surface

Ideal for:

- Field Testing
- **Spot Inspections**
- In-service Inspections
- **Demanding Environments**
- Welding Inspections

Defect Examples:

- **Inclusions**
- Seams
- Shrink cracks
- **Tears**
- Laps
- Welding slags
- Grinding cracks
- Quenching cracks
- Fatigue cracks

May 2018 Page **1** of **2**

Product Properties

Weight	7 lbs. (3.18 kg)
Leg Span	0 – 12 in (0 – 304.8 mm)
Cord Length	10 ft. (3.048 m)
Duty Cycle	50%
Electrical Requirements	115VAC - 50/60 Hz : 6 Amps 230VAC - 50/60 Hz : 3 Amps

Use Recommendations

NDT Method	Magnetic Particle Testing
Recommended	Weight Lift Test Bar – TB10
Accessories	Yoke Light – Y300

Part Numbers

B300 - 115VAC

B300S - 230VAC