

# S-66, S-1212, S-1515

DISTRIBUÉ PAR / DISTRIBUTED BY:

**QNDE**  
QUALITY NDE LTD

**QUEBEC**

164, St-Jean-Baptiste  
Mercier, QC J6R 2C2  
450-691-9090  
info@qn.de.ca

**ONTARIO**

275, Sheldon Drive, Unit 3  
Cambridge, ON N1T 1A3  
519-894-0069  
nadams@qn.de.ca

**ALBERTA**

7307, 50 street NW  
Edmonton, AB T6B 2J9  
587-689-6811  
tfields@qn.de.ca

www.qn.de.ca

1-800-361-3630

## Continuous Duty Demagnetizing Units

The Magnaflux® Demagnetizer's are compact tabletop units designed to be conveniently integrated into an existing magnetic particle inspection system. Oil and waterproof by virtue of their plastic impregnated glass coating, they can be flush mounted to the work surface with supplied angle supports to facilitate easy part insertion by the operator.



### TYPICAL APPLICATIONS

- Demagnetizing parts that have been subjected to Magnavis® and Magnaglo® magnetic particle inspection
- Removing residual magnetism in parts intended for use near magnetic instrumentation
- Demagnetizing parts with bearing or journal surfaces
- Demagnetizing parts after contact with magnetic chucks or lifting magnets

**S-66**

**S-1212**

### PRODUCT PROPERTIES

Unit	S-66	S-1212	S-1515
<b>Foot Print</b>	15.5"L x 9.4"W x 14.4"H (39.4cm x 23.9cm x 36.6cm)	24"L x 11.8"W x 24"H (61cm x 30 cm x 61 cm)	26.5"L x 9.5"W x 25"H (67.31cm x 22.86 cm x 63.5cm)
<b>Weight</b>	85 lb. (38.6kg)	285 lb. (129.3 kg)	575 lb. (260.8 kg)
<b>Magnetizing Current Capacity</b>	4600 A-Turns	7500 A-Turns	8500 A-Turns
<b>Window Size</b>	6" x 6" (15.2cm x 15.2cm)	12" x 12" (31 cm x 31 cm)	15" x 15" (38.1 cm x 38.1 cm)
<b>Available Voltages</b>	115, 230, 460 V	230, 460 V	460 V
<b>Available Frequencies</b>	50 or 60 Hz	50 or 60 Hz	60 Hz