



JR TECHNOLOGY  
LIMITED

REINFORCED PLASTICS  
& COMPOSITES  
PRODUCTION ENGINEERS

SPECIFICATION	WP-632AM HANDPIECE (from 2007 to November 2021)	WP-632AM-R HANDPIECE (from November 2021)
Storage humidity	10 to 90% (without condensation)	10 to 90% (without condensation)
Storage temperature	-40 to 60 degrees C	-40 to 60 degrees C
Operating humidity	10 to 90% (without condensation)	10 to 90% (without condensation)
Operating temperature	0 to 40 degrees C	0 to 40 degrees C
Display	Custom L.C.D. with backlight	Custom L.C.D. with backlight
Weight	350g / 12.8oz – excluding batteries 450g / 15.9oz – including batteries	350g / 12.8oz – excluding batteries 450g / 15.9oz – including batteries
Dimensions	100 x 46 x 276 mm / 3.9 x 1.8 x 10.9"	100 x 46 x 276 mm / 3.9 x 1.8 x 10.9"
Battery type & life	4 x AA, typically 10 hours continuous use, with low battery check	4 x AA, typically 10 hours continuous use, with low battery check
Other functions	Backlit display, 'standard' set-point, go/no-go, review function, data-log up to 1000 data sets, option to download via RS-232, auto-off (12 seconds)	Backlit display, 'standard' set-point, go/no-go, review function, data-log up to 1000 data sets, option to download via RS-232, auto-off (12 seconds) - TBC
Nato Stock Number (NSN)	6635-99-282-4319	TBC
Colour	Grey	Orange
XY Plotter Position	Under unit body	Forward of unit
Expansion	Yes, optional XY plotter	Yes, optional XY plotter & remote probe
USB Connectivity	Yes	Yes

DISTRIBUÉ PAR / DISTRIBUTED BY:



**QUEBEC**

164, St-Jean-Baptiste  
Mercier, QC J6R 2C2  
450-691-9090  
info@qnde.ca



**ONTARIO**

275, Sheldon Drive, Unit 3  
Cambridge, ON N1T 1A3  
519-894-9069  
nadams@qnde.ca

**ALBERTA**

7307, 50 street NW  
Edmonton, AB T6B 2J9  
587-689-6811  
lfields@qnde.ca

[www.qnde.ca](http://www.qnde.ca)

1-800-361-3630