



Industry Leading Warranty



Self-Leveling Camera Heads



100 ft. of Push Rod



512Hz or 640Hz High Power Sonde



For Use with Hathorn® Command Modules



Wi-Fi Reel for Use with Phone or Tablet

Micron DuraCAM camera reels can be used with either Hathorn® control modules (H12+ recommended), or with your own mobile Apple/Android device, should you opt for the Wi-Fi option. The Wi-Fi option is a standalone camera system that allows live streaming and recording to up to three devices at the same time using Hathorn's free app. It is powered by an external Milwaukee®18V or compatible battery (sold separately), which can last over 6 hours.

Micron DuraCAM reels are trusted by plumbers, general contractors, and home inspectors to deliver high definition, recordable video inspections of small pipes 1.5" to 3". These municipal grade reels offer butt-welded steel frame construction and 100ft of premium 1/4" push rod. Both stye of reel come equipped with your choice of DuraCAM 1" or 7/8" straight view camera heads fitted with super bright, cool running LEDs for optimal picture quality.

These features give Micron reels the ultimate in portability and allow you to stay in the field longer. Designed and manufactured in North America, with a full one-year warranty.





PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

Wi-Fi Reel

WMC-1078

7/8"

CAMERA REELS

Micron Wi-Fi Specifications

Display

Size & Type Dependent upon Apple/Android device used

Recording, Storage & Features

Video Recording MPEG4 **Screen Shot JPEG**

File Storage Mobile device, cloud or USB Feet or meters, resettable **Footage Counter**

Sonde Frequency 512Hz

HPDE - 100ft. of 1/4" **Push Rod** Start Up Time ~15 seconds

Power

Battery Only Milwaukee® M18 18V or

equivalent (not included)

Battery Life ~6-8 hrs. using 3.0Ah (sonde off)

AC/DC Adapter 12V 4.1A (included) Wi-Fi Frequency IEEE802.11b/g/n

Standard Micron Specifications

Display

Size & Type Compatible with All Hathorn control modules.

H12+ recommended for best picture & options.

Features

Sonde Frequency High power 512Hz or 640Hz (available only

with H12+ controller)

HPDE - 100ft. of 1/4" **Push Rod**

Recording, Storage & Power Please refer to H12+ specifications

Weight & Dimensions

15lbs. (without battery) 16" x W 12" x 10" Dimension (L x W x H)

Environmental

Water Resistance - Camera and Rod IP68 to 60psi

Water Resistance - Battery Crade **IP65** Water Resistance - Reel Hub **IP63**

Operating Temperature 14°F to 122°F (-10°C to 50°C) **Storage Temperature** -4°F to 140°F (-20°C to 60°C)



100 ft.

1/4

1.5"

3" 16 lbs. 16" x 12" x 10"







Standard Reel



